

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 4:

A01M 29/02, H03K 7/06

(11) International Publication Number:

WO 86/02526

A1

(43) International Publication Date:

9 May 1986 (09.05.86)

(21) International Application Number:

PCT/AU85/00258

(22) International Filing Date:

28 October 1985 (28.10.85)

(31) Priority Application Number:

PG 7858

(32) Priority Date:

26 October 1984 (26.10.84)

(33) Priority Country:

AU

(71) Applicant (for all designated States except US): HI-TEC CONTROL SYSTEMS PTY. LTD. [AU/AU]; 43 Holland Street, Goonellabah, NSW 2480 (AU).

(72) Inventor; and

(75) Inventor/Applicant (for US only): FRY, Alan [AU/AU];
43 Holland Street, Goonellabah, NSW 2480 (AU).


(74) Agent: SIELY, James, Gordon; Arthur S. Cave & Co., Gold Fields House, 1 Alfred Street, Sydney, NSW 2000 (AU). (81) Designated States: AT (European patent), AU, BE (European patent), CH (European patent), DE (European patent), FR (European patent), GB (European patent), IT (European patent), LU (European patent), NL (European patent), SE (European patent), SU, US.

Published

With international search report.

Available Copy

(54) Title: ELECTRONIC FREQUENCY MODULATOR



(57) Abstract

Electronic frequency modulator which combines a lower band frequency with an upper band frequency to produce a square wave output on transmission from a transducer. The present invention can be used as a method of protecting crops from crop pests.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

	•					
AT	Austria		GA	Gabon	MR	Mauritania
λŪ	Australia	•	GB	United Kingdom	MW	Malawi
BB	Barbados		HU	Hungary	NL	Netherlands
BE	Belgium		IT	Italy	NO	Norway .
BG	Bulgaria		JP	Japan	RO	Romania
BR	Brazil		KР	Democratic People's Republic .	SD	Sudan .
CF	Central African Republic			of Korea	SE	Sweden
CG	Congo		KR ·	Republic of Korea	SN	Senegal
CH-	Switzerland		LI	Liechtenstein	ัรบ	Soviet Union
CM	Cameroon		LK.	Sri Lanka	TD	Chad ·
.DE	Germany, Federal Republic of		LU '	Luxembourg	TG	Togo
DK	Denmark	٠.,	MC	Monaco ·	US	United States of America
Fī	Finland	•	MG	Madagascar .	•	
FR	France ·		ML	Mali		

5

10

15

20

25

30

35

ELECTRONIC FREQUENCY MODULATOR

The present invention relates to an electronic frequency modulator of the type wherein a lower band frequency is transmitted on a carrier wave being an upper band frequency. The present invention has particular application in its use as an electronic scarecrow, however it will be apparent to those skilled in the art that the present invention is of wider application as a deterrent to animal and insect crop pests, and is not therefore to be limitively construed by the following detailed description of its use as an electronic scarecrow.

In Australia considerable damage is done to crops and in particular orchards by flying foxes (fruit bats) and birds which descend and devour or damage fruit prior to harvest.

In an average orchard of ten acres containing between three and four thousand fruit trees it is not uncommon for, from two to three million flying foxes, to descend on the orchard and completely devastate the fruit crop and even to break the secondary growth on the trees all within a time span of half an hour.

In order to prevent such destruction of crops, orchardists and growers presently use nets, electric wires and guns in an effort to at least save some of the crop.

These three presently used methods are only partially effective as both electric wires and guns are activated on a periodic cycle and the birds or bats soon learn when the deterrent is non-activated and netting of large areas of orchards or crops is both labour intensive and inefficient in coping with the extreme numbers of birds or bats that can descend on a crop or orchard.

The present invention seeks to substantially overcome or at least ameliorate to a great extent the above disadvantages.

In one broad aspect there is provided an electronic frequency modulator which combines a lower band frequency with an upper band frequency to produce a square wave

10

20

30

output on transmission from a transducer, preferably a peizo ceramic.

In a further aspect of the invention there is provided a method of protecting crops from crop pests using an electronic frequency modulator which combines a lower band frequency with an upper band frequency to produce a square wave output on transmission from a transducer, preferably a peizo ceramic.

The present invention generates acoustically pressurized air waves which affect the muscular and skeletal structure of the bird or bat in flight and the unpleasant sensation causes the bird or bat to divert its flight path to avoid the effect.

Whilst sonic and ultrasonic devices are known and , have been tried in the past as a deterrent against birds and bats, they have proven ineffective because the bird or bat soon realises that it is only a noise and there is nothing physical preventing them from feeding.

Through lengthy trials it was discovered that only a specific modulated frequency corresponding with the bird or bat's wing beat would give an unpleasant effect causing the bird or bat to divert its flight path and avoid the effect. It was found that within certain species not every member of that species would be affected by the one modulated frequency.

The ultrasonic frequency effective in controlling crop pests was found to lie within the following ranges.

marsupials 10 - 25 KHz birds 15 - 35 KHz insects 40 - 80 KHz

Models are presently available for the specific applications as set out below.

•				LOWER BAND	UPPER BAND
· ·				FREQUENCY	FREQUENCY
35	MODEL	CROP PI	EST	INFRASONIC	ULTRASONIC
٠.				CPS	KHZ

815 Crows, galahs, 1-400 17-30 cockatoos

- 3 -

5	MODEL	CROP PEST	LOWER BAND FREQUENCY INFRASONIC CPS	UPPER BAND FREQUENCY ULTRASONIC KHZ	
	825	Starlings,	1-200	25-40	
		leathernecks,	•		
		parrots (certain			
		varieties			
10		only)			
⊹	835	Sheep, cattle,	1-100	20-25	.•
		kangaroos, pigs	•		
	845	Flying foxes,	1-350	20-25	
	• • •	cormorants,		•	•
15	•	pelicans, dogs,			
		egrets,	•		
		night herons,			
	•	ducks			
	855	Rabbits, mice,	1-50	18-30	
20		white tail rats,		<i>;</i>	
		possums, wombats		:	

The present invention will now be described by reference to a preferred embodiment which is illustrated in the attached drawings in which

Fig. 1 is a schematic view of the preferred embodiment in use as an electronic scarecrow.

Fig. 2 is a circuit diagram of the electronic circuitry of the embodiment of Fig. 1.

The electronic scarecrow shown in Fig. 1 is used in a ten acre paddock and is designed to withstand extremes of weather and the normal handling of orchardists and farmers. The electronic scarecrow can be run either continuously or can be preset with a programmable timer to only operate when the crop pests are most prevalent. For larger operations several devices as shown in Fig. 1 can be spaced throughout the orchard or farm.

In Fig. 1 the commercial electronic scarecrow comprises a plurality of known transducer heads 1, mounted on a support column 2 by means of adjustable

BNSDOCID:.<WO. 8602526A1 1 >

25

30

35

10

15

20

mount 3. The support column 2 is stayed to the ground by conventional stays 4 supported on plate 5 on support column 2.

A power supply in the form of a battery 6 is connected to the power pack 7 containing the electronic timer switch, battery level indicator and circuitry as detailed in Fig. 2.

The components as above listed in Fig. 1 with the exception of the circuitry of Fig. 2 are all known and available components.

In Fig. 2 the circuitry comprises the following known electronic components:

R15		10	ohm	1/4	W	resistor
Rl		10	ohm	1/4	W	resistor
R22		10	ohm	1/4	W	resistor

COMPONENT LIST

R28 220 ohm 1/4 w resistor R26 470 ohm. 1/4 w resistor

R14,29,5 1K 1/4 w resistor R18 1.2K 1/4 w resistor

R23 from 1K to 150K fixed component depending on unit, refer to data sheet

Rll 4.7K 1/4 w resistor

R6 4.7K 1/4 w resistor

25 R24 220K 1/4 w resistor

RlO 68K 1/4 w resistor

R30 470K 1/4 w resistor

R27 470K 1/4 w resistor

R9 560K 1/4 w resistor

30 R20 lM w resistor

R3 1.2M 1/4 w resistor

R21 1.5M 1/4 w resistor

R2 1.8M 1/4 w resistor

R17 5.6M 1/4 w resistor

R4,12 110 ohm 1 w resistor
R25 0-25K depending on data sheet attached

R8 0-100K depending on data sheet attached

R19 0-50K depending on data sheet attached

R16 2.7K 1/4 w resistor

35

- 5 -

		- 5 -
	R7N	Not part of main circuit board 3.3 ohms 5 watt
	R13N	Not part of main circuit board 3.3 ohms 5 watt
	C8	TL .001 Ceramic 50V
·	C2 .	TL 470 Ceramic 50V
5	С3	NL .001 G cap 100V
٠.	C 4	TL .01 Ceramic 50V
•	C5	TM .1/50 Monobloc X5V low profile
``	c1	TM .1/50 Monobloc X5V low profile
	C6	NL .01 G cap 100V
10	C7	NL .01 G cap 100V
	D 2	IN 914A-P
	Dl	IN 914A-P
	ICl	555 chips
	IC2	LM3900 chip
15	IC3	566 chip
	TIN	2N3055
	T 7N	2N 3 0 5 5
	T6	2N 29 0 7 A - M
•	T9, 3, 2	BSW64
2.0	T4	DS 557
	· • -	

The present invention is a combination of two frequencies, an upper and a lower band frequency modulated together to produce an FM effect on

25 transmission from a piece of peizo ceramic.

The lower band frequency, referred to as infrasonic

GED44C8.

frequency, is produced through a linear ramp in a 555 IC working as an astable operation which when triggered produces a pulse applied to an IC LM 3900 (op-amp) producing a staircase generation system which ramps down from a 12 volts. A zena diode Dl supplies the offset and prevents pin 5 of the 566 chip approaching the 12 volt locking up the ramp output of T5 producing a linear range of sweep voltage.

The IC3 produces a square wave output in the form


30


of an FM signal which is applied to T9 via pin 3 of IC3 in the required ultrasonic frequencies. The combination is then applied to a common output amp configuration of known circuitry type. The infrasonic signal is to be at the same pulse length as the bird's wing beat. Any alteration to that frequency will have little effect on controlling of birds.

It will be apparent to those skilled in the art that the combination of an infrasonic pulse frequency modulated with an ultrasonic pulse and used as a deterrent for crop pests is unique; and modifications both to the design of the transmitter and the circuitry may be made without departing from the scope of the present invention.

THE CLAIMS:

- 1. An electronic frequency modulator which combines a lower band frequency with an upper band frequency to produce a square wave output on transmission from a transducer.
- 2. An electronic frequency modulator as claimed in claim 1 wherein the transducer is in the form of a peizo ceramic.
- 3. An electronic frequency modulator as claimed in claims 1 or 2 wherein the lower band frequency is pulsed with an upper band frequency pulse.
- 4. A method of protecting crops from crop pests using an electronic frequency modulator which combines a lower band frequency with an upper band frequency to produce a square wave output on transmission from a transducer.
- 5. A method of protecting crops from crop pests as claimed in claim 4 wherein the transducer is a peizo ceramic.
- 6. A method as claimed in claims 4 or 5 wherein the square wave output is of a frequency corresponding to the frequency of the particular crop pests wing beat.
- 7. A method as claimed in claims 4 or 5 wherein the square wave output is of a frequency corresponding to the frequency of the particular crop pests heart beat.
- 8. An electronic frequency modulator as herein described with reference to the attached drawings.
- 9. A method of protecting crops from crop pests as herein described.
- 10. An electronic frequency modulator as claimed in claim 1 to 3 which combines a lower band frequency in the range of 1-500 cps with an upper band frequency in the range of 10-80 kHz.
- 11. A method of projecting crops from crop pests as claimed in claim 4 to 7 which combines a lower band frequency in the range of 1-500 cps with an upper band frequency in the range of 10-80 KHz.





INTERNATIONAL SEARCH REPORT

International Application No PCT/AU 85/00258

CLASSIFICATION OF SUB.	JECT MATTER 1" 11-1-1 2" IANA A CIANA	tione summing action include a reference	
	29/02, HO3K 7/06		
Int. CI. AUIM	23/02, 11038 7700	· · · · · · · · · · · · · · · · · · ·	
FIELDS SEARCHED	Minimum Documentes	uor Searched 1	
lassification System		example Symbols	
			•
IPC A01M	29/02, HO3K 7/00, 7/	/06	•
	Documentation Searched other that to the Estent that such Documents at	on Minimum Documentation re-Included in the Fields Searched #	
AU : IPC as abov	ve, Australian Classii	fication 05.52	
III. DOCUMENTS CONSIDER	KED TO BE RELEVANT		Relevant to Claim No 13
ategory 1 Citation of Doc	ument, 13 with indication, where appro	opriate, of the relevant bassages "	
X,Y AU,B, 62394 (02.04.81)	4/80 (536442) (CARSON) 2 April 1981	(1-5,8-11)
P AU,A, 3599 (13.06.85)	0/84 (ESPANOLA PTY LT	D) 13 June 1985	(1-5,8-11)
X,Y GB,A, 1265 (01.03.72)		ATION) 1 March 1972	·
(27.12.84)		, LTD) 27 December 198	4 (1-5,8-11)
Y Y US.A. 4186	387 (MOSCHGAT) 29 Jan	uary 1980 (29.01.80)	(1-5,8-11)
V V 11C Δ 3872	472 (MOSCHGAT) 18 Mar	ch 1975 (18.03.75)	(1-5,8-11)
	652 (RELLE) 9 October		(1-5,8-11)
			(1-5,8-11)
	733 (PRICE) 24 Januar		(1-5,8-11)
(14.10.58)	586 (NEWSom et al) See Column 2		
X,Y GB,A, 6420 (30.08.50)	97 (SADIR-CARPENTER)	30 August 1950	(1-5,8-11)
			<u> </u>
l considered to be of be	general state of the an which is not included relevance	"T" later document bublished after on pripristy data and not in concrete and not in concrete and the print distance of panicular relevant	cole of theory underlying t
filing date	throw doubts on original claim(s) or objective doubts on original claim(s) or objective do etc.	"A. Bochment of beuticities tate supplies au insentine stab caudat pe countries and	vance; the claimed invent
"P" gocument published 8	an oral disclosure, use, exhibition or	document is combined with ments such combination bet	ng abvious to & person 84.
later than the priority	date Claimed		
IV. CERTIFICATION	on of the International Search.	Date of Mailing of this Internation	Search Report
9 January 1986		<u> </u>	NUARY 1986
Australian Pat		Englose & Authorized Officer	R. TOLHURST

Form PCT/ISA/210 (second sheet) (January 1885)

ANNEX TO THE INTERNATIONAL SEARCH REPORT ON INTERNATIONAL APPLICATION NO. PCT/AU 85/00258

This Annex lists the known "A" publication level patent family members relating to the patent documents cited in the above-mentioned international search report. The Australian Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

Patent Document Cited in Search Report				Patent Family Members				
EP	129415	JP	60002134					
US	4186387	AR .: BR GB	218044 7707384 1555435	AU DE JP	30092/77 2748637 53086376	BE FR NL	860422 2369795 7711886	j.

END OF ANNEX

This Page is Inserted by IFW Indexing and Scanning Operations and is not part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

□ BLACK BORDERS
□ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
□ FADED TEXT OR DRAWING
□ BLURRED OR ILLEGIBLE TEXT OR DRAWING
□ SKEWED/SLANTED IMAGES
□ COLOR OR BLACK AND WHITE PHOTOGRAPHS
□ GRAY SCALE DOCUMENTS
□ LINES OR MARKS ON ORIGINAL DOCUMENT
□ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY

IMAGES ARE BEST AVAILABLE COPY.

OTHER: __

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.